



Gebruikers meeting: JIP Slim malen RTC-Tools developments

Klaudia Horváth

25, April 2018

Outline



- scientific achievements
- full Linge model
- comparison of optimization methods
- closed-loop operation
- pilot results

Scientific production: conferences



European Geosciences Union, General Assembly 2017

A water management decision support system contributing to sustainability

Klaudia Horváth, Bart van Esch, Jorn Baayen, Ivo Pothof, Jan Talsma, Klaas-Jan van Heeringen

SimHydro Conference

Categorization of trapezoidal open channels based on flow conditions for the choice of simple models

Klaudia Horváth, Bart P.M., van Esch, Jorn Baayen

Hydroinformatics Conference

Model predictive control of a river reach with weirs

Klaudia Horváth, Bart van Esch, Jorn Baayen, Ivo Pothof, Jan Talsma, Tjerk Vreeken

Scientific production: journals





La Houille Blanche, International Water Journal: Categorization of trapezoidal open channels based on flow conditions for the choice of simple models

In preparation:


Transactions on Control Systems Technology:

Convex modelling of pumps

Pumping or free flow



Linge




WATERSCHAP VAN DE LINGE
WATER AAN- EN AFVOER 74.000 HA.

Complete model




Name	Location (branch)	Number of pumps and directions	Direction of free flow
Pannerling	1	1 in	In
Kuijk Gemaal	7	4 (3 in 1 out)	In
van Beuningen Gemaal	10	3 out	out
Kolffgemaal	13	3 out	out


35 m³/s inflow to branch 10, where van Beuningen Gemaal is located




35 m³/s inflow to branch 10, where van Beuningen Gemaal is located




11 m³/s inflow to branch 7, where van Kuijkemaal is located





11 m³/s outflow to branch 7, where van Kuijkemaal is located




3 m³/s outflow from Branch 1



1 m³/s outflow from Branch 1



1 m³/s outflow from Branch 1





Why do we need mixed-integer optimization?




3 methods

- Our method: Mixed integer
- Simplified mixed integer
- Continuous



Our method



Head independent power



Continuous optimization







Runtimes and energy







	Proposed method	No head dependence	Continuous
Energy (kWh)	63	146	96
Time (s)	23	29	9

Table 1: Energy consumption of the different methods





Boven-Linge closed-loop







Boven-Linge closed-loop




Boven-Linge closed-loop





Boven-Linge closed-loop




Beneden-Linge





Beneden-Linge






Period: 2013.02.13-2013.02.19





Period: 2013.02.13-2013.02.19





Period: 2013.02.13-2013.02.19



Period: 2013.02.13-2013.02.19



Period: 2013.02.13-2013.02.19



Period: 2013.02.13-2013.02.19

