

Uy-Salto import

Imports data form Web service of Salto Grande: <https://www.saltogrande.org/ws.php?wsdl>.

Available since 2018.02.

Example configuration:

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSpy v2006 rel. 3 sp1 (http://www.altova.com) by Computer Services (WL | Delft Hydraulics) -->
<timeSeriesImportRun xmlns="http://www.wldelft.nl/fews" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://www.wldelft.nl/fews http://fews.wldelft.nl/schemas/version1.0
/timeSeriesImportRun.xsd">
  <import>
    <general>
      <importType>UySalto</importType>
      <serverUrl>https://www.saltogrande.org/ws.php</serverUrl>
<!--      this field is not used, but it is necessary to be able to configure connection timeout-->
      <backupServerUrl>https://www.saltogrande.org/ws.php</backupServerUrl>
<!--      if this field is not configured, it will be set at 2000 automatically. -->
      <connectionTimeOutMillis>100000</connectionTimeOutMillis>
      <user>dummy_username</user>
      <password>dummy_password</password>
      <relativeViewPeriod unit="day" start="-3" end="0" startOverrulable="true" endOverrulable="true"/>
      <idMapId>UySaltoMap</idMapId>
    </general>
    <timeSeriesSet>
      <moduleInstanceId>UySalto</moduleInstanceId>
      <valueType>scalar</valueType>
      <parameterId>paramA</parameterId>
      <locationId>LocB</locationId>
      <timeSeriesType>external historical</timeSeriesType>
      <timeStep unit="nonequidistant"/>
      <readWriteMode>add originals</readWriteMode>
    </timeSeriesSet>
    <timeSeriesSet>
      <moduleInstanceId>UySalto</moduleInstanceId>
      <valueType>scalar</valueType>
      <parameterId>paramB</parameterId>
      <locationId>LocB</locationId>
      <timeSeriesType>external historical</timeSeriesType>
      <timeStep unit="nonequidistant"/>
      <readWriteMode>add originals</readWriteMode>
    </timeSeriesSet>
  </import>
</timeSeriesImportRun>
```